



THERMAL MANAGEMENT HOSES

Helping to control the temperature of your equipment.

Hose Products Division

Thermal Management Hoses

As equipment thermal management requirements evolve, Parker's Hose Products Division continues to meet those connection demands to cool the energy sources and components for an optimal level of performance. Our customers have grown accustomed to Parker leading the world in fluid power and conveyance. Thus, the thermal management product offering follows our tradition of excellence by offering a comprehensive solution strategy.

Product Recommendations By Market

Hose Series	Hose Tube Mtl	Cooling Type	Elec Cooling	Off Hwy Equip	Mining	On Hwy Truck/Bus	Applicable Stds.
807/807XT***	EPDM-P	Liquid Cooling	●	●		●	UL94 V-0
627	EPDM-P	Liquid Cooling	●				UL94 HB
629	EPDM-P	Liquid Cooling	●	●		●	UL94 V-0
*7390	EPDM-P	Liquid Cooling	●				UL94 V-0
*7395	EPDM-P	Liquid Cooling	●	●		●	SAE J20R2 D-1
7391	EPDM-P	Liquid Cooling	●				UL94 V-0
**285	NEOPRENE	Refrigerant	●	●	●	●	SAE J3062 Type C Class 1
**244	BUTYL	Refrigerant	●	●	●	●	SAE J2064 Type B Class 1

Product Recommendations By Size (See individual page for actual ID)

Hose Series	3.5	4	5	6	8	10	12	14	16	20	24	32	48	4"	6"
807/807XT***		●		●	●	●	●		●						
627				●	●		●		●	●	●				
629	●	●													
*7390										●	●	●	●		
*7395				●	●	●	●	●	●						
7391												●	●	●	●
**285		●		●	●	●	●	●	●						
**244									●	●	●				

Product Recommendations By Pressure (Per Size)

Hose Series	3.5	4	5	6	8	10	12	14	16	20	24	32	48	4"	6"
807/807XT***		150		150	150	150	150		100						
627				150	150		150		150	150	150				
629	150	150													
*7390										150	150	150	150		
*7395				150	150	150	150	150	150						
7391												150	150	150	150
**285		500		500	500	500	500	500	500						
**244									500	500	350				

***Note:** E-Z Form is designed to be used in extremely tight bends where traditional products will kink.

****Note:** Not recommended for non-refrigerant applications.

*****Note:** 807XT only available in size -6.

 **WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Hose Products Division

Single Phase Data Center Fitting Portfolio

	629 Server Blade Hose	627 Hose	807 Push-Lok EPDM-P	7395 EZ Form GS Series	7390 EZ Form EPDM-P Hose	7391 EPDM-P S&D Hose
-3.5	N/A					
-4	N/A		82 Series			
-6		HY Series	82 Series			
-8		HY Series	82 Series	HY Series		
-10			82 Series	HY Series		
-12		HY Series	82 Series	HY Series		
-16		HY Series	82 Series	HY Series		
-20		HY Series			HY Series	
-24		43 Series			EZ	N/A
-32					EZ	N/A
3"					N/A	N/A
4"						
6"						



Data Center Hose Application Chart


Sizes (in 16th's)														
Application	Connection Type	Hose Barb & Clamp	Push-Lok	Hose Barb & Clamp	Push-Lok	6 (3/8")			8 (1/2")			12 (3/4")		
						Crimp	Hose Barb & Clamp	Push-Lok	Crimp	Hose Barb & Clamp	Push-Lok	Crimp	Hose Barb & Clamp	Push-Lok
	Server Blade	629	N/A	629	807									
	Jumper Hose					627	627, 7395	807	627, 7395	627, 7395	807			
	CDU Hose											627, 7395	627, 7395	807

Sizes (in 16th's)												
Application	Connection Type	16 (1")			20 (1-1/4")		24 (1-1/2")		32 (2")		48 (3")	
		Crimp	Hose Barb & Clamp	Push-Lok	Crimp	Hose Barb & Clamp	Crimp	Hose Barb & Clamp	Crimp	Hose Barb & Clamp	Crimp	Hose Barb & Clamp
	Server Blade											
	Jumper Hose											
	CDU Hose	627, 7395	627, 7395	807	627, 7390	627, 7390	627, 7390	627, 7390	7390, 7391	7390	7390, 7391	7390, 7391

Push-Lok Assembly and Disassembly Steps

Assembly is easy

1. Cut hose cleanly and squarely with a sharp knife or a Parker Push-Lok cut-off tool.
2. Lubricate the Push-Lok fitting and/or Hose I.D. with a light oil or soapy water only. Do not use heavy oil or grease.
3. Insert fitting into hose until the barb is in the hose.
4. Place end fitting against a flat object (bench or wall). Grip hose approximately one inch from end and push with steady force until the end of the hose bottoms on the fitting and is covered by the yellow plastic cap.



Disassembles fast

1. Leave fitting in place and cut hose lengthwise from the yellow cap approximately one inch.
IMPORTANT: Be careful not to nick barbs when cutting hose.
2. Grip hose and give a sharp downward tug to disengage the fitting.



Caution: Push-Lok fittings will properly grip Push-Lok hose only when pushed all the way in with the cut end of the hose completely concealed by the yellow plastic cap.

Sealing integrity may be damaged by using exterior clamps.

Push-Lok Hose Cutters

Use Parker Push-Lok hose cutters to ensure quick and easy cutting. They are designed for use on all Push-Lok hose sizes and non-wire hose up to 1-1/8" O.D.

TH11 - 1 Hose Cutter

Designed to squarely cut Push-Lok hose 1/4" I.D. through 3/4" I.D.




881540

Hose Cutter with Toggle

This unique tool combines a hose cutter with a toggle action that presses the fitting into the hose, making every job easier, whether you are making one assembly or a hundred. It is designed to handle Push-Lok hose from 1/4" through 3/4".

Overall length: 16"

Weight: approximately 4 pounds



The Most Flexible Route from Hose Application to Hose Installation

E-Z Form™ hose provides extreme flexibility for easy and quick installation of coolant, water and oil suction/return lines on mobile and industrial equipment.

Available in multiple incremental sizes, E-Z Form hose:

- **minimizes the need for costly made-to-order pre-formed hose and metal tubing,**
- **lowers the number of connections and potential leak points,**
- **reduces installation time,**
- **provides rapid delivery from stock and**
- **does not require dedicated inventory.**

Designed to handle extreme bends while allowing full-flow, kink-free performance, E-Z Form hose effectively replaces preformed hoses and hose/bent metal tube assemblies in many applications – eliminating special design, tooling and fabrication costs and associated long lead times. E-Z Form hose is available in three distinct versions, all of which incorporate a helical wire for full suction/vacuum service.

Parker has qualified E-Z Form hose with multiple styles of crimp fittings in popular sizes

and configurations. For fitting and crimp specifications, refer to Crimpsource® at www.parker.com/crimpsource.

Crimpsource provides easy access to all the specifications necessary to correctly fabricate a factory quality hose assembly. You can also print a simple-to-follow data specification sheet or crimper decal.



Off-the-Shelf Convenience and Dramatic Cost Reduction Opportunities

E-Z Form hose is designed and manufactured as a versatile, solution-driven product for OEM and aftermarket-related applications.

Hose Problem

- ☐ Excessive time/labor to design, develop and procure prototypes
- ☐ High cost of made-to-order tooling
- ☐ High cost of low-volume formed hoses and bent metal tubes
- ☐ Multiple leak points inherent in hose/tube combination assemblies
- ☐ Significant time/labor required to install hose/tubes in tight routing applications
- ☐ Other hoses consume more footage due to "rounding out" the required bends
- ☐ Cost of inventory/management/storage of numerous formed hose SKUs
- ☐ Cost of inventory/management/storage of shaped adapters and special fittings

E-Z Form Hose Solution

- ☒ E-Z Form is a catalog product available from stock in multiple incremental sizes
- ☒ One continuous length of hose minimizes leak points and subsequent warranty issues
- ☒ Extreme flexibility streamlines installation and eliminates the need to braze metal tubes
- ☒ Extreme flexibility allows a more direct path in routing
- ☒ Replaces many made-to-order hoses; Packaged in convenient reels and coils and can be cut to length as needed
- ☒ Extreme flexibility permits efficient hose routing while minimizing the need for adapters and/or special fittings

Single Phase Thermal Hose

7395 – E-Z FORM™ GS General Service Hose



[view on web page](#)

Series 7395 hose incorporates a tube that is resistant to commonly used coolant mixtures, a wire helix for full suction/vacuum capability and a path to conduct a static electrical charge to ground, and a cover that is resistant to abrasion, mild chemicals, heat and ozone. The unique Greek cover corrugations are precision-engineered, providing extreme flexibility for routing through confined spaces eliminating the need for formed hose.

NOTE: Do not drag across sharp edges or highly abrasive surfaces.

# Part Number	Hose I.D.		Reinf Layers	Hose O.D.		Approx Wt		Minimum Bend Radius		Max WP		Perm Cplg Rec	Nom Std Pack Qty ft	Pkg Type
	inch	mm		inch	mm	lbs/ft	kg/m	inch	mm	psi	bar			
7395-0375300	3/8	9.5	2	0.8	20.8	0.24	0.36	0.9	24.1	150	10.3	*	300	Reel
7395-0500025	1/2	12.7	2	0.9	23.8	0.27	0.40	0.9	24.1	150	10.3	HY	25	Carton
7395-0500300													300	Reel
7395-0625025	5/8	15.9	2	1.1	27.0	0.33	0.49	1.3	32.7	150	10.3	HY	25	Carton
7395-0625300													300	Reel
7395-0750025	3/4	19.1	2	1.2	30.0	0.35	0.52	1.4	36.3	150	10.3	HY/43	25	Carton
7395-0750300													300	Reel
7395-0875025	7/8	22.2	2	1.3	32.8	0.38	0.57	1.4	36.3	150	10.3	*	25	Carton
7395-0875300													300	Reel
7395-1000025	1	25.4	2	1.4	36.0	0.41	0.61	1.0	25.4	150	10.3	HY/43	25	Carton
7395-1000300													300	Reel
7395-1000300-RED	1	25.4	2	1.4	36.0	0.41	0.61	1.0	25.4	150	10.3	HY/43	300	Reel

Tube: Peroxide cured EPDM for sizes up through 1";
Sulfur cured for sizes above 1"

Reinforcement: Multiple textile braids or plies with wire helix

Cover: Black EPDM; Greek corrugated finish

Temp. Range: -50° F to +257° F (-45° C to +125° C)

Brand Method: Black text on blue stripe and
white text on red stripe

Brand Example: PARKER SERIES 7395 E-Z FORM™ GS
HOSE XXX PSI MAX WP

Design Factor: 4:1


Industry Standards: SAE J20R2-D1 performance
UL94 flame resistance rating HB; through 1"

Applications:

- Air, coolant, mild chemicals, water
 - Coolant systems, drain lines, vacuum service
 - SAE-performance in engine coolant service, general industrial
- Vacuum:** 29" Hg (737 mm Hg)

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

7390 – E-Z FORM™ GS General Service Hose



[view on web page](#)

# Part Number	Hose I.D.		Reinf Layers	Hose O.D.		Approx Wt		Minimum Bend Radius		Max WP		Perm Cplg Rec	Nom Std Pack Qty (ft)	Pkg Type
	inch	mm		inch	mm	lbs/ft	kg/m	inch	mm	psi	bar			
7390-1250100	1 1/4	31.8	2	1.70	44.3	0.50	0.75	1.25	31.8	150	10.3	HY	100	Coils
7390-1500100	1 1/2	38.1	2	1.90	50.5	0.58	0.86	1.50	38.1	150	10.3	EZ	100	Coils
7390-2000100	2	50.8	2	2.50	65.0	0.96	1.43	2.00	50.8	150	10.3	EZ	100	Coils
7390-3000100	3	76.2	2	3.50	90.5	1.51	2.25	3.00	76.2	150	10.3	N/A	100	Coils

Tube: Black EPDM, peroxide cured

Reinforcement: Multiple textile braids or plies with wire helix

Cover: Black synthetic rubber; greek corrugated

Temperature Range: -40°F to +212°F (-40°C to +100°C)

Brand: Mylar Blue (-BLYL) or Red (-RLYL) for color coding

Brand Example: Parker Series 7390 E-Z Form EPDM-P Hose

Design Factor: 4:1

Industry Standards: UL94 V-0 flame resistance rating

Application: DI water and glycol based coolant solutions

Vacuum: Full

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Single Phase Thermal Hose

7391 - EPDM-P Suction & Discharge Hose



[view on web page](#)

# Part Number	Hose I.D.		Reinf Layers	Hose O.D.		Approx Wt		Minimum Bend Radius		Max WP		Perm Cplg Rec	Nom Std Pack Qty ft	Pkg Type
	inch	mm		inch	mm	lbs/ft	kg/m	inch	mm	psi	bar			
7391-2000100	2.0	50.8	2	2.56	65.0	1.09	1.63	7	178	150	10.3	N/A	100	Coils
7391-3000100	3.0	76.2	2	3.58	90.9	1.72	2.57	10	254	150	10.3	N/A	100	Coils
7391-4000100	4.0	101.6	2	4.65	118.1	2.61	3.89	22	559	150	10.3	N/A	100	Coils

Tube: Peroxide cured EPDM

Reinforcement: Multiple textile plies with wire helix

Cover: Synthetic rubber, smooth wrapped cover

Temp. Range: -40° F to +212° F (-40° C to +100° C)

Brand Method: White text on blue stripe

Brand Example: PARKER SERIES 7391 EPDM-P HOSE

Design Factor: 4:1

Industry Standards: UL94 V-0 flame resistance rating

Application: DI water and glycol based coolant solutions

Vacuum: Full (28")

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

807/807XT - Push-Lok EPDM-P

Air/Water/Coolant

Available Cover Colors: BLK RED BLU



[view on web page](#)

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Vacuum Rating		Field Attachable 82 Series
	inch	mm	inch	mm	psi	bar	inch	mm	lbs/ft	kg/m	inches of Hg	kPa	
807-4-BLK-RL	1/4	6.3	0.48	12.2	150	10.3	1.0	25.4	0.08	0.12	15	51	•
807-6-BLK-RL	3/8	9.5	0.63	15.9	150	10.3	1.5	38.1	0.12	0.18	15	51	•
807XT-6-BLK-RL*	3/8	9.5	0.60	15.2	150	10.3	1.6	40.6	0.12	0.18	15	51	•
807-8-BLK-RL	1/2	12.7	0.78	19.8	150	10.3	2.8	69.9	0.18	0.27	15	51	•
807-10-BLK-RL	5/8	15.9	0.91	23.1	150	10.3	3.5	88.9	0.20	0.30	15	51	•
807-12-BLK-RL	3/4	19.1	1.05	26.2	150	10.3	4.5	114.3	0.25	0.37	15	51	•
807-16-BLK-RL	1	25.4	1.28	32.5	100	6.9	6.5	165.1	0.34	0.51	10	34	•

Tube: Black EPDM, peroxide cured

Reinforcement: One fiber braid

Cover: Black, red, and blue, synthetic rubber; smooth finish

Temperature Range: -40°F to +212°F (-40°C to +100°C)

Brand Method: White ink

Brand Example: Parker 807-16 PUSH-LOK EPDM-P;
WP 1MPa (100 psi) 25.4mm (1"); UL94 V-0 HOSE COVER MADE IN USA

Design Factor: 4:1

Industry Standards: UL94 V-0 flame resistance rating

Application: DI water and glycol based coolant solutions, air and phosphate ester

Vacuum: 15 in hg (sizes -4 through -12); 10 in hg (size -16)

Couplings: Designed to be used with 82 series fittings

***Note:** 807XT-6 is approved by OCP for BMQC applications

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Single Phase Thermal Hose

Thermal Cooling Products

627

Thermal Cooling Hose

Parker's 627 is designed to be utilized for the transfer of coolants in high performance computers and data farms. The tube is specially formulated and compounded peroxide cured EPDM for compatibility with industrial coolants.



[view on web page](#)

# Part Number	Hose I.D.		Reinf Layers	Hose O.D.		Approx Wt		Minimum Bend Radius		Max WP		Perm Cplg Rec	Pkg Type
	inch	mm		inch	mm	lbs/ft	kg/m	inch	mm	psi	bar		
627-6-RL	3/8	9.5	2	0.7	16.7	0.13	0.19	1.3	33.0	150	10.3	HY	Reel
627-8-RL	1/2	12.7	4	0.9	22.7	0.24	0.36	2.0	50.8	150	10.3	HY	Reel
627-12-RL	3/4	19.1	4	1.2	29.4	0.34	0.51	3.0	76.2	150	10.3	HY	Reel
627-16-RL	1	25.4	4	1.4	36.3	0.46	0.68	4.5	114.3	150	10.3	HY	Reel
627-20-RL	1 1/4	31.8	4	1.8	45.7	0.67	1.01	6.5	165.1	150	10.3	HY	Reel
627-24-RL	1 1/2	38.1	4	2	50.8	0.84	1.24	9	228.6	150	10.3	43	Reel

Tube: Black EPDM, peroxide cured

Reinforcement: Multiple textile plies

Cover: Black Synthetic Rubber; smooth finish

Temperature Range: -40°F to +212°F (-40°C to +100°C)

Brand Method: White ink

Brand Example: Parker Series 627

Design Factor: 4:1

Industry Standards: UL94 HB flame resistance rating

Application: DI water and glycol-based coolant solutions

Couplings: Designed to be used on hose barb and clamped

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

629

Server Blade Hose

Parker's 629 is designed to be utilized for the transfer of coolants in high performance computers and data farms. The tube is specially formulated and compounded peroxide cured EPDM for compatibility with industrial coolants.



[view on web page](#)

# Part Number	ID		OD		B.R.		WP		Weight		UHg Vacuum Rating		Series Cplg Rec	Std Pack Qty ft	Pkg Type
	(in)	(mm)	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(lbs/ft)	(kg/m)	(in HG)	(kPa)			
629-3.5-RL	0.21	5.3	0.38	9.7	0.6	16.0	150	10.3	0.05	0.07	28	95	N/A	500	Reel
629-4-RL	0.25	6.3	0.44	11.2	0.8	19.1	150	10.3	0.08	0.12	28	95	N/A	600	Reel

Tube: Black EPDM, peroxide cured

Reinforcement: One fiber braid

Cover: Black Synthetic Rubber; smooth finish

Temperature Range: -40°F to +212°F (-40°C to +100°C)

Brand Method: White ink

Brand Example: Parker 629-4 HOSE EPDM-P WP 1MPa (150 psi) 6,4mm (1/4") UL94 V-0 HOSE COVER MADE IN USA

Design Factor: 4:1

Industry Standards: UL94 V-0 flame resistance rating

Application: DI water and glycol-based coolant solutions

Couplings: Designed to be used on hose barb and clamped

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

2-Phase Thermal Hose

Refrigerant Hose Products

285 Refrigerant SAE J3062 TYPE C



[view on web page](#)

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Vacuum Rating		Parkrimp 26 Series
	inch	mm	inch	mm	psi	bar	inch	mm	lbs/ft	kg/m	inches of Hg	kPa	
285-4	3/16	5.1	0.5	12.5	500	34.5	1	25	0.09	0.13	28	95	•
285-6	5/16	8.2	0.6	14.7	500	34.5	1-1/2	40	0.10	0.14	28	95	•
285-8	13/32	10.7	0.7	17.3	500	34.5	2	50	0.13	0.17	28	95	•
285-10	1/2	12.9	0.8	19.4	500	34.5	2-1/2	65	0.15	0.19	28	95	•
285-12	5/8	16.1	0.9	23.6	500	34.5	3	75	0.19	0.27	28	95	•
285-14	3/4	19.1	1.1	27.4	500	34.5	3-1/2	89	0.24	0.34	28	95	•

Application: Refrigerants R134a / PAG Oil & R1234yf / PAG Oil.

Inner Tube: Synthetic rubber with nylon barrier.

Reinforcement: One fiber braid.

Cover: Synthetic rubber.

Temperature Range: -40° F to +257° F (-40° C to +125° C).

Fittings: 26 Series

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

244 Refrigerant SAE J2064 B CLASS I



# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Vacuum Rating		Parkrimp 26 Series
	inch	mm	inch	mm	psi	bar	inch	mm	lbs/ft	kg/m	inches of Hg	kPa	
244-16	7/8	22	1.23	31.2	500	34.5	7-1/2	190	0.51	0.76	28	95	•
244-20	1-1/8	29	1.50	38.1	500	34.5	9	230	0.56	0.83	28	95	•
244-24	1-3/8	35	1.75	44.5	350	34.5	10-1/2	270	0.62	0.92	28	95	•

Application: Refrigerant 134a.

Inner Tube: Butyl rubber.

Reinforcement: One-braid steel wire.

Cover: Fiber braid.

Temperature Range: -22° F to +257° F (-30° C to +125° C).

Fittings: 26 Series.

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

To find catalog information on the multiple fitting series scan the QR Codes which will take you directly to the page.



26 Series



43 Series



82 Series



HY Series



Parker Hannifin Corporation
Hose Products Division
30240 Lakeland Boulevard
Wickliffe, Ohio 44092
phone 440 943 5700
fax 440 943 3129
www.parker.com/hpd

BUL-4480-B215 06/2026

© 2024 Parker Hannifin Corporation

